

# DAILY DRIVEAWAY

## TECHNICAL DESCRIPTION 3.5T LUTON

CHASSIS			STANDARD EQUIPMENT	
DIMENSIONS	Wheelbase (mm)	3750	DAILY BUSINESS	
	GVW (kg)	3500	MANUAL AIR CON	
	GCW (kg)	7000 (inc. 3.5tn towing weight)	FOG LIGHTS	
ENGINE	Model	35S14H	ELECTRIC MIRRORS HTD/ADJ	
	Displacement (l)	2287	CRUISE CONTROL	
	Cylinders	4	12V - 13 PIN PROVISION	
	Power (hp)	136	AIR CONDITIONING COMPRESSOR	
	Torque (Nm)	350		
	Emission	Euro VI HD (Heavy duty)		
GEARBOX	Type	6SPEED 350		
SUSPENSION	Front	Quad-leaf		
	Rear	Reinforced parabolic springs		
TYRES	Brand	Agilis low rolling tyres		
	Dimension	225/65 R16		
SERVICE INTERVALS		2 years /50,000km		

ADDITIONAL EQUIPMENT
DIGITAL BLUETOOTH RADIO (DAB) WITH INTEGRATED FUNCTIONS
ESP SYSTEM + CROSSWIND ASSIST
REVERSE WARNING ALARM
REAR VIEW MIRRORS FOR BODY WIDTH UP TO 2,350 MM
STORAGE CRADLE + USB

BODY	
BODY TYPE	BWS GRP LUTON - Aerodynamic Pod & Fairing
UNDERFRAME	Bolted aluminium channel runners and cross bearers spaced at 610mm
BODY PANELS	17mm lightweight PER panels - White (RAL9010)
REAR FRAME	Powder coated to match body colour
FLOOR	15mm Phenolic coated board fixed to every bearer
ROOF	Continuous GRP skin encased within aluminium radius frame and roof sticks with 600mm spacing
REAR CLOSURE	Narrow Lathe shutter with T lock
SIDE CLOSURE	Not required
UNDERRUN	Supplied with chassis
KICK STRIP	220mm Plywood
INTERNAL RESTRAINT	2 rows Loadlok or Tie Rail
INTERIOR LIGHTS	Internal PIR light
GENERAL	Thermoplastic rear wings, electrics to legal requirements
OPTION AVAILABLE: WITH COLUMN LIFT	Dhollandia 500kg Column lift Aluminium platform, 815mm and 205mm fixed leading edge

NOMINAL DIMENSIONS	BODY INTERNAL	BODY EXTERNAL	COMPLETE VEHICLE*	PAYLOAD	
LENGTH (mm)	3990	4120	6730	PAYLOAD (KG)**	1132
WIDTH (mm)	2040	2080	2080	PAYLOAD WITH COLUMN LIFT (KG)**	987
HEIGHT (mm)	2212	2370	3140		

\*without column lift

\*\*payload subject to variance due to engineering tolerances